

SPECIFICATIONS

“DOUGLAS” MODEL 2566

RACK, PAN, AND UTENSIL WASHER

DESIGN AND OPERATION	Designed for batch type operation where the wash rack is loaded with items to be cleaned. After the door is closed, the short, medium or long wash cycle is selected then which initiates a 150° F. recirculating detergent wash followed by a 180° F. final fresh water sanitizing rinse. The final sanitizing rinse water flows into the recirculated wash tank for reuse and freshening causing excess water to overflow to drain. A buzzer and unload light indicates cycle completion. The door is then reopened for unloading and reloading for the next cycle. Booster heaters maintain proper operating temperatures.
CABINET	70” wide x 90” deep (100” for pass through option) x 101 1/2” high (128 1/2” overall clearance height when floor mounted, 114 1/2” when used in a pit. Add 7” with gas heated rinse tank). Door Opening: 38” wide x 84” high. Wash Chamber: 38” wide x 72” deep x 84” high. Constructed of #14 gauge, 300 Series STAINLESS STEEL with a #3 finish. All seams are tig or mig welded. Seams, where needed for watertight construction, are continuously welded. All other seams are stitch welded for strength. All welds are cleaned inside, cleaned and buffed outside. Optional continuous welds in lieu of stitch welds available.
DOOR	Constructed of #16 and #18 gauge, 300 Series STAINLESS STEEL with a #3 finish. Door is double skinned with integral framework for additional strength. Standard right hand, or optional left hand swing, equipped with external latch, inside release handle and is interlocked to prevent machine operation while open.
WASHER FLOOR	Constructed of #12 gauge STAINLESS STEEL formed sheets designed to provide maximum strength. Supports constructed of 2” x 2” x 1/4” STAINLESS STEEL angle.
RECIRCULATING WASH TANK	Constructed of #14 gauge, 300 Series STAINLESS STEEL, heated by 42 KW electric immersion heaters (gas, live steam or steam coil options are available). Complete with low water protection, automatic fill, 1 1/4” NPT overflow connection, 2” gate drain valve, thermometer, pressure gauge and is thermostatically controlled. 180 gallon tank capacity, sloped to drain.
WASH PUMP	Closed coupled centrifugal wash pump, bronze fitted with cast iron casing. Complete with 25 H.P. ODP motor (optional TEFC or wash down duty motors available). 208/240/480 or optional 575 volt, 3 phase, 60 cycle. Rated for 430 gallons per minute at 35 to 45 PSI. Optional STAINLESS STEEL wet end available.
ROTATING WASH HUB ASSEMBLY	Water driven, STAINLESS STEEL spray arm assembly with STAINLESS STEEL jets, removable end caps and hand operated quick release mechanism for easy cleaning and reassembly.
FILTRATION	Perforated STAINLESS STEEL screen type. Double filter system for increased effectiveness and easy cleaning without emptying wash tank.

SANITIZING PUMPED RINSE TANK	Constructed of #14 gauge, 300 Series STAINLESS STEEL, heated by 36 KW electric immersion heaters (infrared gas or steam coil options are available). Complete with low water protection, automatic fill, and thermostatically controlled to provide 20 gallons per 30 second cycle at 20 PSI and has a 60 gallon capacity. Also supplied with a closed coupled centrifugal pump with STAINLESS STEEL casing and impeller. 1 1/2 H.P. ODP motor (optional TEFC or wash down duty motors available) 208/240/480 or optional 575 volt, 3 phase, 60 cycle.
FINAL RINSE PIPING	300 Series STAINLESS STEEL tubing with brass compression fittings and full cone rinse jets. Optional STAINLESS STEEL fittings and jets are available .
CONTROL AND INFORMATION CENTER	Electrical control panel is NEMA 12 STAINLESS STEEL or optional NEMA 4X STAINLESS STEEL with Square "D" components. 120 volt control circuit with push pad operation of "POWER ON", "STOP", and "SHORT, MEDIUM, or LONG WASH CYCLES". A digital display indicates "TIME REMAINING" for each cycle. LEDs indicate wash, rinse, and unload functions. A buzzer is also included to provide an audible indication of time to unload. A pre-programmed circuit board allows the push pad to be used as a "DIAGNOSTIC CENTER" by displaying "ERROR CODES" for ease of troubleshooting. Moisture resistant gauges measure temperature and pressure for recirculated wash and final rinse. NOTE: Optional NEMA 4X STAINLESS STEEL panel with push button control and internal adjustable timers is available in lieu of digital push pad operation.
EXTERNAL RINSE HOSE	Externally mounted rinse hose with spray gun for easy cleaning and maintenance of machine.
STEAM EXHAUST VENT	Steam exhaust vent 12 7/8" I.D. consisting of #16 gauge rolled collar for PVC pipe connection bolted to the top of the machine. Machine pre-wired with control timer for the addition of a fan.
OPTIONAL EXHAUST FAN	One (1) 12" diameter fan with 12 7/8" I.D. collar mounted on washer to extract excess steam after final rinse cycle. Constructed of STAINLESS STEEL housing and aluminum blade with 1/4 H.P. TEFC or optional wash down duty motor, 120 volt, 1 phase, 1725 RPM, rated 500 CFM at .5" static pressure. Optional fan with STAINLESS STEEL housing and blade is available.
OPTIONAL HOOD AND EXHAUST FAN ASSEMBLY	STAINLESS STEEL hood with 15" diameter fan mounted over door and activates upon door opening to evacuate steam that escapes. Constructed of STAINLESS STEEL housing and blade with 1 1/2 H.P. TEFC or optional wash down duty motor, 208/240/480 or optional 575 volt, 3 phase, 60 cycle, 3450 RPM, rated for 2700 CFM at .8" static pressure.
RACKS	Customized to hold your specific items. Constructed of STAINLESS STEEL rod and formed angle, mig welded. Supplied with STAINLESS STEEL casters and nylon wheels, fixed front and swiveled rear.
CONNECTIONS	Water Inlet: 1" NPT, 120° F. Drain: 2" NPT Overflow: 1 1/4" NPT Steam Option: (1) 3/4" NPT or (2) 3/4" NPT with optional steam heated rinse tank Steam Condensate: (1) 3/4" NPT or (2) 3/4" NPT with optional steam heated rinse tank Gas Option: (1) 3/4" NPT or (2) 3/4" with optional gas heated rinse tank Electrical: Two-point connection, except for 575 volt, which is a single-point.
UTILITIES	See attached Utilities Chart for service requirements specific to various combinations of wash and rinse tank heating.



UTILITY CHART

“DOUGLAS” MODEL 2566

RACK, PAN, AND UTENSIL WASHER

120 Volt - 1 Phase, 5 Running Amps, 15 Amp Service Breaker plus one of the following (except for 575 volt, which is a single point connection):

**ELECTRIC HEATED
WASH TANK,
ELECTRIC HEATED
RINSE TANK**

208 Volt - 3 Phase, 305 Running Amps, 400 Amp Minimum Service Breaker
240 Volt - 3 Phase, 277 Running Amps, 350 Amp Minimum Service Breaker
480 Volt - 3 Phase, 139 Running Amps, 175 Amp Minimum Service Breaker
575 Volt - 3 Phase, 112 Running Amps, 150 Amp Minimum Service Breaker

**GAS HEATED
WASH TANK,
ELECTRIC HEATED
RINSE TANK**

208 Volt - 3 Phase, 188 Running Amps, 250 Amp Minimum Service Breaker
240 Volt - 3 Phase, 172 Running Amps, 225 Amp Minimum Service Breaker
480 Volt - 3 Phase, 86 Running Amps, 110 Amp Minimum Service Breaker
575 Volt - 3 Phase, 69 Running Amps, 90 Amp Minimum Service Breaker

Gas Consumption: 180,000 BTUs per hour. Supply Pressure: Minimum 7” w.c. for natural, 11” w.c. for propane and 14” w.c. maximum.

**GAS HEATED
WASH TANK,
INFRARED GAS
HEATED RINSE TANK**

208 Volt - 3 Phase, 72 Running Amps, 90 Amp Minimum Service Breaker
240 Volt - 3 Phase, 67 Running Amps, 90 Amp Minimum Service Breaker
480 Volt - 3 Phase, 34 Running Amps, 45 Amp Minimum Service Breaker
575 Volt - 3 Phase, 27 Running Amps, 35 Amp Minimum Service Breaker

Gas Consumption: 360,000 BTUs per hour. Supply Pressure: Minimum 7” w.c. for natural, 11” w.c. for propane and 14” w.c. maximum.

**STEAM HEATED
WASH TANK,
ELECTRIC HEATED
RINSE TANK**

208 Volt - 3 Phase, 188 Running Amps, 250 Amp Minimum Service Breaker
240 Volt - 3 Phase, 172 Running Amps, 225 Amp Minimum Service Breaker
480 Volt - 3 Phase, 86 Running Amps, 110 Amp Minimum Service Breaker
575 Volt - 3 Phase, 69 Running Amps, 90 Amp Minimum Service Breaker

Steam Consumption: 170 lbs. per hour at 15 PSI minimum.

**STEAM HEATED
WASH TANK,
STEAM HEATED
RINSE TANK**

208 Volt - 3 Phase, 72 Running Amps, 90 Amp Minimum Service Breaker
240 Volt - 3 Phase, 67 Running Amps, 90 Amp Minimum Service Breaker
480 Volt - 3 Phase, 34 Running Amps, 45 Amp Minimum Service Breaker
575 Volt - 3 Phase, 27 Running Amps, 35 Amp Minimum Service Breaker

Steam Consumption: 345 lbs. per hour at 15 PSI minimum.

For single-point connection option for 208, 240, or 480 volt, add 2 running amps to total and recalculate service breaker size, which should be at least 125% of total running amps.

Please add the following running amps to those noted above for an optional hood and fan assembly (4.9 at 208 volt, 4.2 at 240 volt, 2.1 at 480 volt, and 1.5 at 575 volt) and recalculate service breaker size, which should be at least 125% of total running amps.